

VT604G Switched PDU

- Remotely device On/Off switching
- Redundant Power & Network

Ethernet
1Gb/s
Update!



Specifications

CPU Speed / RAM / OS	2 cores, 720mHz / 128Mb / Linux v.6.2
Ethernet	10/100/1000 Mbit/s
Outlets	x4 C13 outlets, 110-240V AC, 50/60 Hz.
Inlet	C14 inlet, 110-240V AC, 50/60Hz, Fuse 10A
Reserve power	12V DC terminal
USB micro	For USB camera, USB flash, USB hub
Analog ports	x2 ports for sensors (extendable using CAN)
CAN port	Connect up to x32 sensors & devices
Dry Contact inputs	x2 dry contact inputs
LAN	Ethernet 10/100 Base-T port
Relays (12V DC)	x2 outputs, 0.25A each
SD card slot	Up to 512 Gb SDHC
LTE slot modem	Ethernet, SMS (modem ordered separately)
Mounting	19" 1U (brackets included)
Extension slot	VT485m Modbus RTU extension slot or VT485r OSDPV2 reader extension slot
Battery extension slot	VT-ACCU Rechargeable reservation battery or VT-BAT Reservation battery 6F22 9V
Warranty	3 years
Support	On-line portal



Supports

- Centralized Monitoring & Control**
 - Responsive Web Interface
 - SNMP v1, v2c, v3
- Scalability**
 - Extension units, LTE modem, OSDPV2, Modbus
 - Modbus TCP/IP, 4-20mA, 0-10V, Analog, CAN
- Improved security**
 - OpenVPN, SSL, HTTPS
 - Three-tier data access permissions with login
- Protocol support**
 - DHCP, HTTP, HTTPS, DynDNS, SMTP, RADIUS, Syslog, NTP server, HTTP request
- API**
 - XML, JSON
- System Usability**
 - Multi-language mobile interface
 - First-time wizard
 - Sensor graphing for single & multiple sensors
- Virtual sensors / devices / elements**
 - PING, Timers, Triggers, Logic schemes, IP cameras, Groups, Math, SNMP GET
- Notifications and alerts**
 - E-mail, SMS, Phone dial, SNMP Traps, SMS link, Web-to-SMS,
- Logging**
 - SD card, USB flash, E-mail, FTP